


Portable potentiostat model CS100 without EIS



The CS100 is internally powered by a lithium battery, which can be placed in a glove box or used outdoors. The lithium battery can be charged in advance, and the Type-C interface is used for charging and communication. The circuit adopts a floating-ground design, and the electrochemical parameters of the grounding system can be measured without an isolation transformer.

CS100 portable potentiostat is mainly used for battery testing, electroanalytical chemistry, and corrosion electrochemical testing. The voltage control range is $\pm 10\text{V}$, compliance voltage is $\pm 12\text{V}$, the current output range is $\pm 45\text{mA}$, and the minimum current resolution can reach 100fA .


Features

- Small and light, portable and convenient
- Simple to install and easy to operate.
- High accuracy, current resolution is 100fA, and measurement accuracy is 0.1% of the range.
- Internal lithium battery facilitates the outdoor on-site measurement
- The circuit adopts a floating-ground design



Applications

- The small and convenient potentiostat can be used for performance testing of battery materials in the glove box;
- Ultra-low detection limit of heavy metal ions, suitable for water quality testing in environmental protection;
- High current accuracy, suitable for small current detection in biosensor;
- Comprehensive functions, can be used for the active ingredients detection in food and drug field;
- Easy to carry, suitable for bridge corrosion and soil corrosion measurements



Voltammetry stripping curves

Overview


The CS100 portable potentiostat is composed of DDS digital signal synthesizer, constant potential control, dual-channel high-speed 16bit/high-precision 24bit AD converter. The built-in DDS and dual-channel signal correlation integral circuit improves the measurement accuracy of AC impedance. CS100 potentiostat can also output sine wave, square wave, triangle wave, sawtooth wave, pulse wave, etc., and the output frequency is 0~100KHz.

The command control and data analysis of the CS100 portable potentiostat are realized through the CS Studio software. The software has multi-coordinate graphic display and zooming, data/graphic storage/printing, and interactive help. The software has techniques for materials and corrosion electrochemistry, including automatic or manual reverse sweep of passivation curve, electrochemical reactivation method, solution resistance (IR drop)

measurement and compensation.

CS Studio software also has a complete data analysis function, which can achieve the volt-ampere curve smoothing, the peak height and area integration, and the electrochemical parameters analysis of the polarization curve, including polarization resistance R_p , Tafel slope b_a , b_c , and corrosion current density i_{corr} , corrosion rate calculation, etc., noise resistance R_n and power spectrum can also be calculated, and the graph can be copied to other files in vector mode.

The CS100 portable can be controlled by either our desktop software or App.



Specifications

Communication: USB or Bluetooth

Power supply: built-in li-battery 6000mAH@3.7V / USB

Size / weight: 150mm x 90mm x 30mm, 500g

Support 2-, 3-or 4-electrode system

Potential control range: $\pm 10V$

Maximum current: $\pm 45mA$

Compliance voltage: $\pm 12V$

Potential accuracy: $0.1\% \times$ full range

Minimum potential resolution: $10\mu V$

Current accuracy: $0.1\% \times$ full range

Minimum current resolution: $100fA$

Potential range: $\pm 2.5\text{V}$, $\pm 5\text{V}$, $\pm 10\text{V}$

Current range: 200pA~50mA, 10 ranges

(200pA, 2nA, 20nA, 200nA, 2uA, 20uA, 200uA, 2mA, 20mA, 50mA)

Reference electrode input impedance: $10^{13}\Omega \parallel 8\text{pF}$

AC amplitude: $0 \sim \pm 2.5\text{V}$

Signal response bandwidth: 1MHz

Max. acquisition rate: 150,000 data points/s

CV and LSV scan rate: 0.001mV~ 10V/s

Electrochemical techniques

Stable polarization

- Open Circuit Potential (OCP)
- Potentiostatic (I-T curve)
- Galvanostatic
- Potentiodynamic (Tafel plot)
- Galvanodynamic (DGP)

Transient Polarization

- Multi Potential Steps
- Multi Current Steps
- Potential Stair-Step (VSTEP)
- Galvanic Stair-Step (ISTEP)

Chrono Method

- Chronopotentiometry (CP)
- Chronoamperometry (CA)
- Chronocoulometry (CC)

Voltammetry

- Linear Sweep Voltammetry (LSV)
- Cyclic Voltammetry (CV)
- Staircase Voltammetry (SCV)
- Square Wave Voltammetry (SWV)
- Differential Pulse Voltammetry (DPV)
- Normal Pulse Voltammetry (NPV)#
- Differential Normal Pulse Voltammetry (DNPV)
- AC Voltammetry (ACV)
- 2nd harmonic AC Voltammetry (SHACV)
- Fourier Transform AC Voltammetry (FTACV)

Amperometric

- Differential Pulse Amperometry (DPA)
- Double Differential Pulse Amperometry (DDPA)
- Triple Pulse Amperometry (TPA)
- Integrated Pulse Amperometric Detection (IPAD)

Stripping Voltammetry

- Potentiostatic Stripping

- Linear Stripping
- Staircase Stripping
- Square Wave Stripping
- Differential Pulse Voltammetry Stripping
- Normal Pulse Voltammetry Stripping
- Differential Normal Pulse Voltammetry Stripping

Corrosion Measurements

- Cyclic polarization curve (CPP)
- Linear polarization curve (LPR)
- Electrochemical Potentiokinetic Reactivation (EPR)
- Electrochemical Noise (EN)
- Zero resistance Ammeter (ZRA)

Battery test

- Battery Charge and Discharge
- Galvanostatic Charge and Discharge (GCD)
- Potentiostatic Charging and Discharging(PCD)
- Potentiostatic Intermittent Titration Technique(PITT)
- Galvanostatic Intermittent Titration Technique(GITT)

Extensions

- Data Logger
- Electrochemical Stripping/ Deposition
- Bulk Eletrolysis with Coulometry (BE)
- Rs measurement

Portable Potentiostat/Galvanostat model CS100 (without EIS)

Standard supply:

portable potentiostat CS100 *1

Software *1

Power cable, USB cable *1, Electrode cable *2,

Dummy cell *1

Contact us

Yushan Zhang

Wuhan Corrttest Instruments Corp., Ltd.

Add: #505, Jinfeng Bld. A, International Enterprise Center, Optics valley Ave.,East lake High-tech Dev. Zone, Wuhan city, 430074, China

E-mail: sales2@corrtest.com.cn

Mob./whatsapp: (+86)13469965984

Website: <https://www.corrtestinstruments.com/en>, <http://www.corrtest.com.cn/en>